# NSN 5950-01-323-6904

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-323-6904

# **Reliability Indicator:**

Not established

#### **Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

# **Overall Length:**

1.600 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.180 inches single mounting facility single center group

# **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.180 inches single mounting facility single center group

#### **Overall Height:**

1.100 inches

#### **Overall Width:**

1.600 inches

#### Frequency Rating:

100.0 kilohertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

# **Maximum Operating Temp:**

130.0 degrees celsius

# Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded hole single group

# Winding Function And Quantity:

1 primary single component and 2 secondary single component

# **Features Provided:**

Tinned wire leads

#### **Thread Size:**

0.112 inches single group

# **Winding Operating Current:**

35.0 milliamperes dc single component single primary

# **Winding Operating Voltage:**

260.00 ac volts single component single primary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

4 wire hook and 2 wire lead

#### Shelf Life:

N/a

# NSN 5950-01-323-6904

Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A058b0