## NSN 5950-01-323-6904

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-323-6904

Poliobility Indicatory
Reliability Indicator: Not established
Hazardous Locations/environmental Protection:
Moisture resistant and vibration resistant
Overall Length:
1.600 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.180 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.180 inches single mounting facility single center group
Overall Height:
1.100 inches
Overall Width:
1.600 inches
Frequency Rating:
100.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Operating Temp:
130.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Features Provided:
Tinned wire leads
Thread Size:
0.112 inches single group
Winding Operating Current:
35.0 milliamperes dc single component single primary
Winding Operating Voltage:
260.00 ac volts single component single primary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 wire hook and 2 wire lead
Shelf Life:

N/a

## NSN 5950-01-323-6904

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

