

View Online at <https://aerobasegroup.com/nsn/5950-01-324-1131>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 0.896 inches and 0.916 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.896 inches single mounting facility single center group and 0.916 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.242 inches single mounting facility single center group and 0.262 inches single mounting facility single center group

**Overall Height:**

Between 1.290 inches and 1.330 inches

**Overall Width:**

Between 0.896 inches and 0.916 inches

**Frequency Rating:**

100.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Operating Temp:**

130.0 degrees celsius

**Mounting Tab Width:**

Between 0.002 inches and 0.022 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Tab single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Winding Operating Current:**

630.0 milliamperes ac single component single primary and 1.6 amperes ac single component single primary

**Winding Power Rating:**

93.6 volts-amperes single component 3rd secondary

**Winding Operating Voltage:**

72.00 ac volts single component 2nd secondary

**Special Features:**

One primary winding and five secondary windings

**Test Data Document:**

16340-11-00091 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

14 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0