

View Online at <https://aerobasegroup.com/nsn/5950-01-324-1131>

Reliability Indicator:

Not established

Overall Length:

Between 0.896 inches and 0.916 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.896 inches single mounting facility single center group and 0.916 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.242 inches single mounting facility single center group and 0.262 inches single mounting facility single center group

Overall Height:

Between 1.290 inches and 1.330 inches

Overall Width:

Between 0.896 inches and 0.916 inches

Frequency Rating:

100.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius

Mounting Tab Width:

Between 0.002 inches and 0.022 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Tab single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Winding Operating Current:

630.0 milliamperes ac single component single primary and 1.6 amperes ac single component single primary

Winding Power Rating:

93.6 volts-amperes single component 3rd secondary

Winding Operating Voltage:

72.00 ac volts single component 2nd secondary

Special Features:

One primary winding and five secondary windings

Test Data Document:

16340-11-00091 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0