NSN 5950-01-324-2387

Radio Frequency Coil - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-324-2387 |
|---|
| Reliability Indicator: |
| Not established |
| Hazardous Locations/environmental Protection: |
| Fungus resistant and corrosion resistant and vibration resistant |
| Mounting Hole Diameter: |
| 0.200 inches single group |
| Inductance Rating: |
| 843.00 microhenries single component single winding |
| Coil Form Type: |
| Solid single component |
| Core Construction: |
| S0lid single component |
| Body Length: |
| 0.550 inches |
| Overall Diameter: |
| 1.150 inches |
| Maximum Operating Temp: |
| 120.0 degrees celsius |
| End Application: |
| 5805-01-188-3993 central office, telephone, automatic |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 1 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Conductor Size: |
| 0.02535 inches american wire gage single component single winding |
| Winding Operating Current: |
| 1.6 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.300 single component single winding |
| Test Data Document: |
| 16340-11-00033 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 2 wire lead |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5950-01-324-2387

Radio Frequency Coil - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0