

View Online at <https://aerobasegroup.com/nsn/5950-01-324-2402>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and corrosion resistant and vibration resistant

Mounting Hole Diameter:

0.300 inches single group

Inductance Rating:

100.80 microhenries single component all winding

Frequency Rating:

100.0 kilohertz single component

Core Construction:

Solid single component

Body Length:

0.700 inches

Overall Diameter:

1.600 inches

Maximum Operating Temp:

120.0 degrees celsius

End Application:

5805-01-188-3993 central office, telephone, automatic

Winding Quantity:

3 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component all winding

Winding Conductor Size:

0.03196 inches american wire gage single component all winding

Winding Operating Current:

11.9 amperes dc single component all winding

Dc Resistance Rating In Ohms:

0.035 single component all winding

Winding Operating Voltage:

27.00 ac pounds per hour wet single component all winding

Test Data Document:

16340-11-00057 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0