# NSN 5950-01-324-4288

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-324-4288

# **Reliability Indicator:**

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and corrosion resistant and vibration resistant

# Inductance Type:

Fixed

#### **Inductance Rating:**

2.20 millihenries single component single winding

#### **Frequency Rating:**

400.0 hertz single component

#### **Body Length:**

0.500 inches

#### **Overall Diameter:**

1.120 inches

#### Maximum Operating Temp:

85.0 degrees celsius

End Application:

5805-01-188-3993 central office, telephone, automatic

#### Winding Quantity:

1 single component

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Terminal single group

**Rating Method:** 

Electrical single component single winding

## Winding Operating Current:

500.0 milliamperes dc single component single winding

## Dc Resistance Rating In Ohms:

0.613 single component single winding

## **Test Data Document:**

16340-11-00079 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A058b0