

View Online at <https://aerobasegroup.com/nsn/5950-01-324-4291>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

5.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.625 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.969 inches single mounting facility single center group and 2.031 inches single mounting facility single center group

**Overall Height:**

3.250 inches

**Mounting Slot Width:**

0.180 inches single group and 0.190 inches single group

**Frequency Rating:**

47.5 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Core grounded single component

**Body Width:**

2.500 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**End Application:**

5805-01-188-3993 central office, telephone, automatic

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

50.0 amperes ac single component single primary

**Winding Operating Voltage:**

200.00 ac pounds per hour wet single component single secondary

**Test Data Document:**

28528-1135688 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 tab, solder lug and 2 wire lead w/lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0