

View Online at <https://aerobasegroup.com/nsn/5950-01-324-4291>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

5.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.969 inches single mounting facility single center group and 2.031 inches single mounting facility single center group

Overall Height:

3.250 inches

Mounting Slot Width:

0.180 inches single group and 0.190 inches single group

Frequency Rating:

47.5 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded single component

Body Width:

2.500 inches

Maximum Operating Temp:

105.0 degrees celsius

End Application:

5805-01-188-3993 central office, telephone, automatic

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

50.0 amperes ac single component single primary

Winding Operating Voltage:

200.00 ac pounds per hour wet single component single secondary

Test Data Document:

28528-1135688 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug and 2 wire lead w/lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0