

View Online at <https://aerobasegroup.com/nsn/5950-01-324-9574>

Reliability Indicator:

Not established

Overall Length:

Between 2.780 inches and 2.785 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.395 inches single mounting facility all center groupings and 2.405 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.155 inches single mounting facility all center groupings and 1.165 inches single mounting facility all center groupings

Overall Height:

Between 1.975 inches and 2.025 inches

Overall Width:

Between 1.530 inches and 1.570 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to mounting single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches all groupings

Winding Operating Current:

733.0 milliamperes ac single component single secondary

Winding Power Rating:

16.6 volts-amperes single component single secondary

Winding Operating Voltage:

22.70 ac volts single component single secondary

Test Data Document:

04939-717801569 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0