

View Online at <https://aerobasegroup.com/nsn/5950-01-326-0603>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.490 inches 1st mounting facility single center group and 1.510 inches 1st mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.390 inches 1st mounting facility single center group and 1.410 inches 1st mounting facility single center group

Mounting Hole Diameter:

0.265 inches 2nd group and 0.272 inches 2nd group

Inductance Rating:

40.00 microhenries single component single winding

Frequency Rating:

4.8 kilohertz single component

Core Construction:

Solid single component

Body Length:

Between 2.180 inches and 2.220 inches

Body Width:

Between 2.120 inches and 2.160 inches

Body Height:

Between 2.280 inches and 2.320 inches

Maximum Operating Temp:

170.0 degrees celsius

Distance Between Mounting Facility Centers:

2.500 inches 2nd mounting facility single center group and 2.940 inches 2nd mounting facility single center group

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 1st group

Mounting Method:

Unthreaded hole 2nd group

Rating Method:

Electrical single component single winding

Thread Size:

0.138 inches 1st group

Winding Operating Current:

30.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.001 single component single winding

Winding Operating Voltage:

3.00 ac volts single component single winding

Test Data Document:

08748-tf51-145 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc 1st group

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0