

View Online at <https://aerobasegroup.com/nsn/5950-01-326-2285>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group and 1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.125 inches single mounting facility single center group and 1.250 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded to secondary terminal single component

Body Length:

Between 1.813 inches and 1.938 inches

Body Width:

Between 1.687 inches and 1.812 inches

Body Height:

Between 2.313 inches and 2.438 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

3.0 amperes ac single component single secondary

Winding Operating Voltage:

105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 125.00 ac volts single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 turret and 2 wire lead

Specification Data:

81349-mil-t-27/300 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0