

View Online at <https://aerobasegroup.com/nsn/5950-01-326-7667>

Reliability Indicator:

Not established

Overall Length:

3.200 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.470 inches single mounting facility single center group and 2.530 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.345 inches single mounting facility single center group and 2.405 inches single mounting facility single center group

Overall Height:

1.750 inches

Overall Width:

2.750 inches

Frequency Rating:

40.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

2.3 amperes ac single component single primary

Winding Power Rating:

151.8 volts-amperes single component single primary

Winding Operating Voltage:

28.00 ac volts single component single primary and 66.00 ac volts single component single primary

Test Data Document:

53711-5859675 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0