NSN 5950-01-329-1741

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-329-1741

Reliability Indicator:
Not established
Inductance Type:
Fixed
Inductance Rating:
25.00 microhenries single component all winding
Frequency Rating:
10.0 kilohertz single component
Body Length:
0.360 inches
Overall Diameter:
0.500 inches
Maximum Operating Temp:
130.0 degrees celsius
End Application:
Aircraft, stratofortress b-52; tank, abrams m-1; navstar global positioning system user equipment (ue)
Winding Quantity:
2 single component
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Electrical single component all winding
Winding Operating Current:
2.7 amperes dc single component all winding
Dc Resistance Rating In Ohms:
0.043 single component all winding
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Test Data Document:
81349-mil-prf-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 wire lead
Specification Data:
81349-mil-prf-27/356 government specification
Shelf Life:
N/a

-

Unit Of Measure:

NSN 5950-01-329-1741

Reactor - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A058b0

Mil-std (military Standard):

Mil-prf-27 spec.