

View Online at <https://aerobasegroup.com/nsn/5950-01-329-9516>

Reliability Indicator:

Not established

Overall Length:

Between 1.144 inches and 1.164 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.344 inches single mounting facility single center group and 0.364 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.033 inches single mounting facility single center group and 1.053 inches single mounting facility single center group

Overall Height:

1.476 inches

Overall Width:

Between 1.033 inches and 1.053 inches

Frequency Rating:

100.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

120.0 degrees celsius

Mounting Tab Width:

Between 0.002 inches and 0.022 inches

End Application:

Central office, telephone auto

Inclosure Type:

Fully enclosed

Mounting Method:

Tab single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Power Rating:

600.0 volts-amperes single component single secondary

Winding Operating Voltage:

600.00 ac volts single component single secondary

Test Data Document:

16340-11-00066 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0