

View Online at <https://aerobasegroup.com/nsn/5950-01-329-9517>

Reliability Indicator:

Not established

Overall Length:

Between 1.813 inches and 1.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.359 inches single mounting facility single center group and 1.391 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.234 inches single mounting facility single center group and 1.266 inches single mounting facility single center group

Overall Height:

2.813 inches

Overall Width:

Between 1.687 inches and 1.812 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

400.0 milliamperes ac single component 1st secondary

Winding Power Rating:

5.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

12.00 ac volts single component 1st secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 wire hook

Specification Data:

81349-mil-t-27/326 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0