

View Online at <https://aerobasegroup.com/nsn/5950-01-330-0579>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

9.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.940 inches single mounting facility single center group and 5.060 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.940 inches single mounting facility single center group and 5.060 inches single mounting facility single center group

Overall Height:

7.000 inches

Overall Width:

5.500 inches

Mounting Slot Width:

0.297 inches single group and 0.327 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

8.26 amperes ac single component single secondary

Winding Power Rating:

19.5 volts-amperes single component single primary

Winding Operating Voltage:

90.00 ac volts single component single primary and 150.00 ac volts single component single primary

Test Data Document:

03956-1808601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0