

View Online at <https://aerobasegroup.com/nsn/5950-01-330-0579>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

9.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.940 inches single mounting facility single center group and 5.060 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.940 inches single mounting facility single center group and 5.060 inches single mounting facility single center group

**Overall Height:**

7.000 inches

**Overall Width:**

5.500 inches

**Mounting Slot Width:**

0.297 inches single group and 0.327 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Delta-delta

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

8.26 amperes ac single component single secondary

**Winding Power Rating:**

19.5 volts-amperes single component single primary

**Winding Operating Voltage:**

90.00 ac volts single component single primary and 150.00 ac volts single component single primary

**Test Data Document:**

03956-1808601 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0