# NSN 5950-01-330-7680

Reactor-transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-330-7680

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.790 inches single mounting facility single center group and 0.810 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.790 inches single mounting facility single center group and 0.810 inches single mounting facility single center group

#### **Overall Width:**

1.100 inches

#### **Inductance Rating:**

34.00 microhenries single component single winding

#### Frequency Rating:

125.0 kilohertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

1.100 inches

### **Body Height:**

1.220 inches

# **Maximum Operating Temp:**

130.0 degrees celsius

# Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

2 single group

# **Mounting Method:**

Threaded hole single group

# **Rating Method:**

Electrical single component single winding

#### **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### **Thread Size:**

0.112 inches single group

# **Winding Operating Current:**

7.0 amperes dc single component single winding

# **Winding Operating Voltage:**

12.02 ac volts single component single winding

#### **Test Data Document:**

13973-865530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

6 wire lead

# NSN 5950-01-330-7680

Reactor-transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0