

View Online at <https://aerobasegroup.com/nsn/5950-01-330-7680>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.790 inches single mounting facility single center group and 0.810 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.790 inches single mounting facility single center group and 0.810 inches single mounting facility single center group

Overall Width:

1.100 inches

Inductance Rating:

34.00 microhenries single component single winding

Frequency Rating:

125.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.100 inches

Body Height:

1.220 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

7.0 amperes dc single component single winding

Winding Operating Voltage:

12.02 ac volts single component single winding

Test Data Document:

13973-865530 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0