

View Online at <https://aerobasegroup.com/nsn/5950-01-330-8657>

Reliability Indicator:

Not established

Turn Quantity:

20 single component 1st secondary 4 single component 2nd secondary 100 single component single primary

Inductance Rating:

200.00 microhenries single component 1st secondary 1.73 millihenries single component single primary

Frequency Rating:

15.0 kilohertz single component and 25.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

0.810 inches

Body Outside Diameter:

0.950 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single primary and winding turns single component single primary electrical single component all secondary and winding turns single component all secondary

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Conductor Size:

0.00795 inches american wire gage single component single primary 0.02010 inches american wire gage single component all secondary

Winding Operating Current:

0.1 amperes ac single component single primary

Dc Resistance Rating In Ohms:

0.025 single component 1st secondary 0.010 single component 2nd secondary 1.500 single component single primary

Winding Operating Voltage:

2.00 ac pounds per hour with retaining chain single component 1st secondary 10.90 ac pounds per hour dry single component single primary and 19.50 ac pounds per hour with retaining chain single component single primary

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0