

View Online at <https://aerobasegroup.com/nsn/5950-01-330-8657>

**Reliability Indicator:**

Not established

**Turn Quantity:**

20 single component 1st secondary 4 single component 2nd secondary 100 single component single primary

**Inductance Rating:**

200.00 microhenries single component 1st secondary 1.73 millihenries single component single primary

**Frequency Rating:**

15.0 kilohertz single component and 25.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

0.810 inches

**Body Outside Diameter:**

0.950 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single primary and winding turns single component single primary electrical single component all secondary and winding turns single component all secondary

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Winding Conductor Size:**

0.00795 inches american wire gage single component single primary 0.02010 inches american wire gage single component all secondary

**Winding Operating Current:**

0.1 amperes ac single component single primary

**Dc Resistance Rating In Ohms:**

0.025 single component 1st secondary 0.010 single component 2nd secondary 1.500 single component single primary

**Winding Operating Voltage:**

2.00 ac pounds per hour with retaining chain single component 1st secondary 10.90 ac pounds per hour dry single component single primary and 19.50 ac pounds per hour with retaining chain single component single primary

**Terminal Type And Quantity:**

7 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0