NSN 5950-01-330-8659

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-330-8659
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
3.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.590 inches single mounting facility single center group and 2.610 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.140 inches single mounting facility single center group and 2.160 inches single mounting facility single center group
Overall Height:
1.775 inches
Overall Width:
2.600 inches
Frequency Rating:
16.7 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Operating Temp:
155.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 4 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Voltage:
41.85 ac volts single component 4th secondary
Special Features:
Terminal 17 is internally connected to terminal 3; terminal 18 is internally connected to terminal 1; terminal 19 is internally connected to
terminal 2; terminal 13 and 14 are internally connected dummy terminals
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
13 turret
Shelf Life:
N/a

__

Unit Of Measure:

NSN 5950-01-330-8659

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0