## NSN 5950-01-330-8660

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-330-8660

View Offline at https://defobasegroup.com/nsh/0330-01-330-0000
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant and salt spray resistant
Overall Length:
1.400 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.080 inches single mounting facility single center group and 1.100 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.080 inches single mounting facility single center group and 1.100 inches single mounting facility single center group
Overall Height:
1.650 inches
Overall Width:
1.400 inches
Frequency Rating:
25.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Operating Temp:
155.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Thread Size:
0.112 inches single group
Winding Operating Current:
6.0 amperes ac single component 1st secondary
Winding Operating Voltage:
81.30 ac volts single component 3rd secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
10 turret
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-330-8660

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0