

View Online at <https://aerobasegroup.com/nsn/5950-01-330-8706>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Salt spray resistant and vibration resistant

Overall Length:

1.400 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.080 inches single mounting facility single center group and 1.100 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.080 inches single mounting facility single center group and 1.100 inches single mounting facility single center group

Overall Height:

1.650 inches

Overall Width:

1.400 inches

Frequency Rating:

25.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Power Rating:

28.28 volts-amperes single component single secondary

Winding Operating Voltage:

28.28 ac volts single component single primary

Test Data Document:

13973-841325 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0