NSN 5950-01-330-8783

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-330-8783

Reliability Indicator:	Relia	ability	' Indi	cator:
------------------------	-------	---------	--------	--------

Not established

Hazardous Locations/environmental Protection:

Fungus proof

Overall Length:

5.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.105 inches single mounting facility all center groupings and 4.145 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.480 inches single mounting facility all center groupings and 2.520 inches single mounting facility all center groupings

Overall Height:

6.800 inches

Overall Width:

3.500 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta and wye-wye

Maximum Transformer Power Rating:

550.0 volt-ampere single component

Winding Shielding Method:

Inclosure grounded single component

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 1st group

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.190 inches all groupings

Winding Operating Current:

22.7 amperes ac single component all secondary

Winding Operating Voltage:

24.20 ac volts single component all secondary

Thread Series Designator:

Unf all groupings

NSN 5950-01-330-8783

Power Transformer - Page 2 of 2



Terminal '	Type And	Quantity:
ı errillinar	I VDE AIIU	Qualitity.

11 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0