

View Online at <https://aerobasegroup.com/nsn/5950-01-331-0550>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.690 inches single mounting facility single center group and 0.710 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.440 inches single mounting facility single center group and 0.460 inches single mounting facility single center group

Overall Width:

0.750 inches

Inductance Type:

Fixed

Inductance Rating:

50.00 microhenries single component single winding and 80.00 microhenries single component single winding

Frequency Rating:

30.0 kilohertz single component

Body Height:

0.800 inches

Maximum Operating Temp:

90.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Thread Size:

0.112 inches single group

Winding Operating Current:

1.0 amperes dc single component single winding and 8.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.018 single component single winding

Test Data Document:

13973-841304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0