

View Online at <https://aerobasegroup.com/nsn/5950-01-331-2834>

Reliability Indicator:

Not established

Overall Length:

7.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.970 inches 2nd mounting facili type 2nd center group and 5.030 inches 2nd mounting facili type 2nd center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.740 inches 2nd mounting facili type 2nd center group and 3.760 inches 2nd mounting facili type 2nd center group

Overall Height:

10.750 inches

Overall Width:

6.000 inches

Inductance Type:

Swinging

Inductance Rating:

5.00 millihenries single component single winding and 80.00 millihenries single component single winding

Frequency Rating:

141.0 hertz single component

Maximum Operating Temp:

155.0 degrees celsius

Distance Between Mounting Facility Centers:

3.900 inches 1st mounting facili type 1st center group

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 2nd group

Mounting Method:

Threaded stud 2nd group

Rating Method:

Electrical single component single winding

Thread Size:

0.250 inches 1st group

Winding Operating Current:

35.0 amperes dc single component single winding

Special Features:

Terminals split for dual connection

Test Data Document:

13973-841322 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0