

View Online at <https://aerobasegroup.com/nsn/5950-01-331-2834>

**Reliability Indicator:**

Not established

**Overall Length:**

7.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.970 inches 2nd mounting facili type 2nd center group and 5.030 inches 2nd mounting facili type 2nd center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.740 inches 2nd mounting facili type 2nd center group and 3.760 inches 2nd mounting facili type 2nd center group

**Overall Height:**

10.750 inches

**Overall Width:**

6.000 inches

**Inductance Type:**

Swinging

**Inductance Rating:**

5.00 millihenries single component single winding and 80.00 millihenries single component single winding

**Frequency Rating:**

141.0 hertz single component

**Maximum Operating Temp:**

155.0 degrees celsius

**Distance Between Mounting Facility Centers:**

3.900 inches 1st mounting facili type 1st center group

**Winding Quantity:**

1 single component

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

6 2nd group

**Mounting Method:**

Threaded stud 2nd group

**Rating Method:**

Electrical single component single winding

**Thread Size:**

0.250 inches 1st group

**Winding Operating Current:**

35.0 amperes dc single component single winding

**Special Features:**

Terminals split for dual connection

**Test Data Document:**

13973-841322 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc all groupings

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0