

View Online at <https://aerobasegroup.com/nsn/5950-01-331-2840>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

3.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.115 inches single mounting facility single center group and 3.135 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

Overall Height:

1.550 inches

Overall Width:

2.000 inches

Frequency Rating:

33.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 7 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

49.5 amperes ac single component 4th secondary

Winding Operating Voltage:

49.49 ac volts single component 2nd secondary

Special Features:

2 primary windings; 7 secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 turret and 3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0