NSN 5950-01-331-3167

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-331-3167

Reliability Indicator:

Not established

Overall Length:

9.200 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.885 inches single mounting facility single center group and 7.915 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.185 inches single mounting facility single center group and 6.215 inches single mounting facility single center group

Overall Height:

4.700 inches

Frequency Rating:

45.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Width:

7.500 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.312 inches single group

Winding Operating Current:

24.0 amperes ac single component single secondary

Winding Power Rating:

78.0 volts-amperes single component single primary

Winding Operating Voltage:

21.18 ac volts single component single secondary

Test Data Document:

13973-841330 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

NSN 5950-01-331-3167

Power Transformer - Page 2 of 2



Terminal	Type	And	Quantity:
-----------------	------	-----	-----------

8 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0