

View Online at <https://aerobasegroup.com/nsn/5950-01-331-3908>

Reliability Indicator:

Not established

Overall Length:

0.600 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.375 inches single mounting facility single center group

Overall Width:

0.560 inches

Frequency Rating:

10.0 hertz single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Height:

0.540 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

28.2 milliamperes ac single component 1st secondary

Dc Resistance Rating In Ohms:

0.700 single component 1st secondary

Winding Operating Voltage:

70.70 ac millivolts single component 2nd secondary

Test Data Document:

13973-841289 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

7 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0