## NSN 5950-01-331-3910

Reactor - Page 1 of 1

A058b0



View Online at https://aerobasegroup.com/nsn/5950-01-331-3910
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Humidity resistant and vibration resistant
Mounting Hole Diameter:
0.182 inches single group and 0.192 inches single group
Inductance Type:
Swinging
Inductance Rating:
1.50 millihenries single component single winding and 3.00 millihenries single component single winding
Body Length:
1.900 inches
Overall Diameter:
1.625 inches
Maximum Operating Temp:
100.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding
Winding Conductor Size:
0.03196 inches american wire gage single component single winding
Winding Operating Current:
1.2 amperes dc single component single winding and 2.4 amperes dc single component single winding
Test Data Document:
27963-13212183 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: