

View Online at <https://aerobasegroup.com/nsn/5950-01-331-3921>

Reliability Indicator:

Not established

Overall Length:

Between 4.470 inches and 4.550 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.740 inches single mounting facility single center group and 3.760 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

Overall Height:

Between 3.720 inches and 3.800 inches

Overall Width:

Between 3.550 inches and 3.800 inches

Mounting Hole Diameter:

0.208 inches single group and 0.228 inches single group

Frequency Rating:

45.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

18.0 amperes ac single component single secondary

Winding Power Rating:

504.0 volts-amperes single component single secondary

Winding Operating Voltage:

28.00 ac volts single component single secondary

Test Data Document:

13973-841354 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0