

View Online at <https://aerobasegroup.com/nsn/5950-01-331-3921>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 4.470 inches and 4.550 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.740 inches single mounting facility single center group and 3.760 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

**Overall Height:**

Between 3.720 inches and 3.800 inches

**Overall Width:**

Between 3.550 inches and 3.800 inches

**Mounting Hole Diameter:**

0.208 inches single group and 0.228 inches single group

**Frequency Rating:**

45.0 hertz single component and 66.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Maximum Operating Temp:**

155.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

18.0 amperes ac single component single secondary

**Winding Power Rating:**

504.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

28.00 ac volts single component single secondary

**Test Data Document:**

13973-841354 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0