

View Online at <https://aerobasegroup.com/nsn/5950-01-331-3922>

Reliability Indicator:

Not established

Overall Length:

4.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

Overall Height:

2.270 inches

Overall Width:

3.850 inches

Mounting Hole Diameter:

0.181 inches single group and 0.201 inches single group

Frequency Rating:

45.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Operating Current:

500.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

7.42 volts-amperes single component 2nd secondary

Winding Operating Voltage:

9.50 ac volts single component 1st secondary

Test Data Document:

13973-841355 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0