NSN 5950-01-331-4084

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5050-01-331-4084

View Online at https://aerobasegroup.com/nsn/5950-01-331-4084
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
0.520 inches
Turn Quantity:
200 single component single secondary
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.400 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.400 inches single mounting facility single center group
Overall Width:
0.520 inches
Inductance Rating:
180.00 millihenries single component single primary and 360.00 millihenries single component single primary
Frequency Rating:
65.0 kilohertz single component and 105.0 kilohertz single component
Coil Form Type:
Solid single component
Body Height:
0.375 inches
Maximum Operating Temp:
125.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Electrical single component single primary and winding turns single component single primary
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Conductor Size:
0.00315 inches american wire gage single component single secondary
Test Data Document:
13499-646-3137 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 pin
Shelf Life:
N/a

Unit Of Measure:

NSN 5950-01-331-4084

Radio Frequency Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0