## NSN 5950-01-331-7004

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-331-7004

Reliability	/ Indicator:
-------------	--------------

Not established

### **Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group

## **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.590 inches single mounting facility single center group and 0.610 inches single mounting facility single center group

#### **Inductance Rating:**

100.00 microhenries single component all winding

#### Frequency Rating:

15.75 kilohertz single component

**Body Length:** 

Between 1.240 inches and 1.300 inches

**Body Width:** 

Between 0.940 inches and 1.000 inches

**Body Height:** 

Between 0.800 inches and 0.900 inches

### **Maximum Operating Temp:**

90.0 degrees celsius

## **Winding Quantity:**

2 single component

## Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

2 single group

## **Mounting Method:**

Threaded hole single group

## **Rating Method:**

Electrical single component all winding

## Thread Size:

0.112 inches single group

## **Winding Operating Current:**

7.0 amperes dc single component all winding

### Dc Resistance Rating In Ohms:

0.050 single component all winding

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

4 wire lead

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5950-01-331-7004

Reactor - Page 2 of 2



em			

No

Fiig:

A058b0