

View Online at <https://aerobasegroup.com/nsn/5950-01-331-7010>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Corrosion resistant and vibration resistant

Overall Length:

9.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.490 inches single mounting facility single center group and 7.510 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.240 inches single mounting facility single center group and 7.260 inches single mounting facility single center group

Overall Width:

8.530 inches

Mounting Hole Diameter:

0.380 inches single group and 0.400 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-wye

Winding Shielding Method:

Internally shielded single component

Body Height:

5.155 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

6.5 amperes ac single component single primary

Winding Power Rating:

747.5 volts-amperes single component single primary

Winding Operating Voltage:

52.33 ac pounds per hour wet single component 2nd secondary

Terminal Type And Quantity:

15 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0