

View Online at <https://aerobasegroup.com/nsn/5950-01-331-7786>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant and humidity resistant

Overall Length:

15.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.250 inches single mounting facility single center group

Overall Height:

6.880 inches

Overall Width:

8.630 inches

Mounting Slot Width:

0.440 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

5.0 kilovolt-ampere single component

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

41.0 amperes ac single component all secondary

Winding Operating Voltage:

120.00 ac volts single component all primary

Test Data Document:

30003-1217as310 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0