

View Online at <https://aerobasegroup.com/nsn/5950-01-331-7786>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant and humidity resistant

**Overall Length:**

15.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

8.250 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

7.250 inches single mounting facility single center group

**Overall Height:**

6.880 inches

**Overall Width:**

8.630 inches

**Mounting Slot Width:**

0.440 inches single group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

5.0 kilovolt-ampere single component

**Winding Shielding Method:**

Primary and secondary shielded and brought out to terminal single component

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

2 primary single component and 2 secondary single component

**Winding Operating Current:**

41.0 amperes ac single component all secondary

**Winding Operating Voltage:**

120.00 ac volts single component all primary

**Test Data Document:**

30003-1217as310 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0