

View Online at <https://aerobasegroup.com/nsn/5950-01-332-1122>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.250 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

13.000 inches

Body Width:

7.250 inches

Body Height:

5.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

8 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

10.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single secondary and 120.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

1 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0