NSN 5950-01-332-2666

Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-332-2666

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.240 inches single mounting facility single center group and 1.260 inches single mounting facility single center group

Frequency Rating:

2.4 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.770 inches

Body Width:

1.590 inches

Body Height:

1.630 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Features Provided:

Tinned wire leads

Thread Size:

0.112 inches single group

Winding Operating Current:

1.5 amperes ac single component single primary output

Winding Operating Voltage:

0.50 ac volts single component single primary output

Test Data Document:

08748-tf51-029 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

1 wire lead and 2 wire lead w/lug

Shelf Life:

N/a

NSN 5950-01-332-2666

Power Autotransformer Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0