Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-332-2666

# **Reliability Indicator:**

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.990 inches single mounting facility single center group and 1.010 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.240 inches single mounting facility single center group and 1.260 inches single mounting facility single center group

#### **Frequency Rating:**

2.4 kilohertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

**Body Length:** 

1.770 inches

Body Width:

1.590 inches

Body Height:

1.630 inches

#### Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

### Winding Function And Quantity:

1 primary, fixed autotransformer type single component

# **Features Provided:**

Tinned wire leads

**Thread Size:** 

0.112 inches single group

### Winding Operating Current:

1.5 amperes ac single component single primary output

#### Winding Operating Voltage:

0.50 ac volts single component single primary output

#### Test Data Document:

08748-tf51-029 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

1 wire lead and 2 wire lead w/lug

# Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0