

View Online at <https://aerobasegroup.com/nsn/5950-01-332-3696>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.490 inches single mounting facility single center group and 0.510 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.740 inches single mounting facility single center group and 0.760 inches single mounting facility single center group

Frequency Rating:

10.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.750 inches

Body Width:

1.130 inches

Body Height:

1.300 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Thread Size:

0.112 inches single group

Winding Operating Current:

100.0 milliamperes ac single component single primary output

Winding Operating Voltage:

1.00 ac volts single component single primary output

Test Data Document:

08748-tf51-039 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 wire lead and 1 wire lead w/lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0