NSN 5950-01-332-5683

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-332-5683

| Reliability Indicator: |
|---|
| Not established |
| Turn Quantity: |
| 5 single component all winding |
| Inductance Type: |
| Swinging |
| Inductance Rating: |
| 1.50 microhenries single component all winding and 2.30 microhenries single component all winding |
| Frequency Rating: |
| 5.0 kilohertz single component |
| Body Length: |
| 0.740 inches |
| Body Outside Diameter: |
| 0.820 inches |
| Winding Quantity: |
| 8 single component |
| Inclosure Type: |
| Open |
| Mounting Method: |
| Terminal single group |
| Rating Method: |
| Electrical single component all winding and winding turns single component all winding |
| Features Provided: |
| Tinned wire leads |
| Winding Conductor Size: |
| 0.03196 inches american wire gage single component all winding |
| Winding Operating Current: |
| 38.0 amperes dc single component all winding |
| Dc Resistance Rating In Ohms: |
| 0.012 single component all winding |
| Terminal Type And Quantity: |
| 16 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |