

View Online at <https://aerobasegroup.com/nsn/5950-01-332-9937>

**Reliability Indicator:**

Not established

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Transformer Winding Connection Type:**

Wye-delta-wye

**Maximum Transformer Power Rating:**

600.0 volt-ampere single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

Between 4.880 inches and 4.920 inches

**Body Width:**

Between 2.180 inches and 2.220 inches

**Body Height:**

Between 4.880 inches and 4.920 inches

**Maximum Operating Temp:**

170.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

6 2nd group

**Mounting Method:**

Threaded hole all groupings

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.138 inches all groupings

**Winding Operating Current:**

10.0 amperes ac single component all secondary

**Winding Operating Voltage:**

28.00 ac volts single component all secondary

**Test Data Document:**

08748-tf51-007 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc all groupings

**Terminal Type And Quantity:**

4 wire lead w/lug and 6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0