

View Online at <https://aerobasegroup.com/nsn/5950-01-332-9937>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta-wye

Maximum Transformer Power Rating:

600.0 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 4.880 inches and 4.920 inches

Body Width:

Between 2.180 inches and 2.220 inches

Body Height:

Between 4.880 inches and 4.920 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 2nd group

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches all groupings

Winding Operating Current:

10.0 amperes ac single component all secondary

Winding Operating Voltage:

28.00 ac volts single component all secondary

Test Data Document:

08748-tf51-007 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

4 wire lead w/lug and 6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0