## NSN 5950-01-333-0105

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-333-0105

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Overall Length:
0.700 inches
Turn Quantity:
35 single component single winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.600 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.330 inches single mounting facility single center group
Overall Height:
0.700 inches
Overall Width:
0.430 inches
Inductance Type:
Fixed
Inductance Rating:
100.00 microhenries single component single winding
Frequency Rating:
10.0 kilohertz single component
Maximum Operating Temp:
60.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Method:
Plug-in single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Features Provided:
Tinned wire leads
Winding Conductor Size:
0.02535 inches american wire gage single component single winding
Dc Resistance Rating In Ohms:
50.000 single component single winding
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a

## NSN 5950-01-333-0105

Reactor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0