NSN 5950-01-333-4921

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-333-4921

Reliability Indicator:
Not established
Overall Length:
1.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches single mounting facility single center group
Overall Height:
1.225 inches
Overall Width:
1.000 inches
Mounting Hole Diameter:
0.140 inches single group
Inductance Type:
Fixed
Inductance Rating:
3.60 microhenries single component single winding
Frequency Rating:
10.0 kilohertz single component
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding
Winding Operating Current:
16.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.015 single component single winding
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Test Data Document:

33604-2-18556 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 5950-01-333-4921

Reactor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0